

F203 Donut Loadcell

Standard Ranges 400 and 800kN (40 and 80tonnef)

- ✓ Hardened stainless steel body
- ✓ Sealed to IP65
- ✓ Standard 1 year warranty
- ✓ Tensile applications are 'fail-safe'
- ✓ Very high structural load limit
- ✓ Traceable calibration with certificate included in the standard price



Specification

Parameter	Value	Unit
Non-linearity - Terminal	±0.25	% RL
Hysteresis	±0.25	% RL
Creep - 20 minutes	±0.05	% AL
Repeatability	±0.02	% RL
Rated output - Nominal	1.2	mV/V
Rated output - Rationalised	1.0	mV/V
Rationalisation tolerance	±0.5	% RL
Zero load output	±4	% RL
Temperature effect on rated output per $\hat{A}^{\circ}\text{C}$	±0.005	% AL
Temperature effect on zero load output per $\hat{A}^{\circ}\text{C}$	±0.03	% RL
Temperature range - Compensated	-10 to +50	$^{\circ}\text{C}$
Temperature range - Safe	-10 to +80	$^{\circ}\text{C}$
Excitation voltage - Recommended	10	V
Excitation voltage - Maximum	20	V
Bridge resistance	700	$\hat{\Omega}$
Insulation resistance - Minimum at	500	M $\hat{\Omega}$

50Vdc		
Overload - Safe	50	% RL
Overload - Ultimate	400	% RL
Sealing	IP65	
Weight - Nominal (excluding cable)	5 to 5.5	kg
All standard ranges are manufactured in stainless steel.		

F203 - Geometry: Axial strain cylinder in a sealed case, with raised end load bearing faces and hole right through. For use in compression or in fail-safe tensile applications.

The F203 is ideally suited to engineering force measurements including through centre safety testing of cables, rods and bolts. It is designed for easy installation, usually between two flat faces bearing on its loading rings, either unattached or with retaining spigots positioned in the centre hole. Alternatively tensile load transfer can be achieved via a tie rod assembly through the centre hole. In this way the loadcell can indirectly measure tensile loads in a "fail-safe" mode. We are happy to design variants of this loadcell to meet your specific requirements. Versions can be manufactured for operation up to +250°C. Please consult our engineering department.

Order Codes

Code	Description
F203CFR0K0	Compression, IP65, unrationalised
F203CFR0KN	Compression, IP65, rationalised

Structural Stiffness - Nominal

Range (kN)	Stiffness (N/m)
400	1 x 1010
800	2 x 1010

Notes

- AL = Applied load.
- RL = Rated load.
- Temperature coefficients apply over the compensated range.
- The load must be applied directly through the central loading axis.

Connections

The loadcell is fitted with 2 metres of PVC insulated 4 core screened cable type 16-2-4C.


Excitation + = Red, Excitation - = Blue, Signal + = Yellow, Signal - = Green, Screen = Orange.

The screen is not connected to the loadcell body.

Files

Type	Title	Download
STEP File	F203CFR0K0 400kN (40tonnef)	Download
STEP File	F203CFR0K0 800kN (80tonnef)	Download
STEP File	F203 400kN Loadbutton	Download
STEP File	F203 800kN Loadbutton	Download

Outline



Novatech Measurements Limited

83 Castleham Road, St Leonards on Sea, East Sussex, TN38 9NT, England.

Telephone: +44 (0)1424 852744

Fax: +44 (0)1424 853002

E-mail: info@novatechloadcells.co.uk